













Nozzles for application with exhaust extractors



Below are listed all sorts of nozzles for exhaust extractors.

While selecting, take into account the diameter, material and equipment.


Sort of nozzle	Type	Part no.	Connection diameter [mm]	Inlet dimension [mm]	Weight [kg]	Remarks	Cooperating devices
	SZGO-125	819S28	125	Ø150	2,5	Rubber circular nozzle, with lever gripper, manual disconnection.	ALAN-N, OBS/P, OBP/P-AL, OBP/P, GLOBAL
	SZGO-150	819S29	150	Ø170	3,2		
	SZGO-125-N	819S27	125	Ø150	2,2	Polyethylene circular nozzle, with lever gripper, manual disconnection.	ALAN-N, OBS/P, OBP/P-AL, OBP/P, GLOBAL
	SZGO-150-N	819S31	150	Ø170	2,25		
	SZGP-100	819S18	100	180x100	2,1	Rubber oval nozzle, with lever gripper, manual disconnection.	ALAN-N, OBS/P, OBP/P-AL, OBP/P, GLOBAL
	SZGP-125	819S19	125	180x100	3,2		
	SZGO-125/S	819S75	125	Ø150	2,5	Rubber circular nozzle, with lever gripper and steel cable for automatic disconnection.	OBP/P
	SZGO-150/S	819S76	150	Ø170	3,2		
	SZGO-125/S-N	819S14	125	Ø150	2,2	Polyethylene circular nozzle, with lever gripper and steel cable for automatic disconnection.	OBP/P
	SZGO-150/S-N	819S15	150	Ø170	2,25		
	SZGP-100/S	819S77	100	180x100	2,1	Rubber oval nozzle, with lever gripper and steel cable for automatic disconnection.	OBP/P
	SZGP-125/S	819S78	125	180	3,2		
	SZGO-125/B	819S70	125	Ø150	2,5	Rubber circular nozzle, with lever gripper and Bowden cable for automatic disconnection.	OBP/P-AL, OBP/P
	SZGO-150/B	819S71	150	Ø170	3,2		
	SZGO-125/B-N	819S16	125	Ø150	2,2	Polyethylene circular nozzle, with lever gripper and Bowden cable for automatic disconnection.	OBP/P-AL, OBP/P
	SZGO-150/B-N	819S17	150	Ø170	2,25		
	SZGP-100/B	819S72	100	180x100	2,1	Rubber oval nozzle, with lever gripper and Bowden cable for automatic disconnection.	OBP/P-AL, OBP/P
	SZGP-125/B	819S73	125	180x100	3,2		
	SRGP-100	819S33	100	180x100	2,3	Rubber oval nozzle for built-up, covered exhaust pipes, manual disconnection (gripper is inside the exhaust pipe).	ALAN-N, OBS/P, OBP/P-AL, OBP/P, GLOBAL
	SRGP-125	819S34	125	180x100	2,4		
	AN-100	819S06	100	Ø125	1	Metallic nozzle, knob gripper, for manual disconnection.	ALAN-N, OBS/P, GLOBAL
	AN-125	819S07	125	Ø125	1,2		
	AN-150	819S08	150	Ø150	1,45		
	AN-200	819S00	200	Ø200	2		
	D-100	819S09	100	Ø100	1,3	Metallic nozzle, spring retracted shut-off cover, for manual disconnection.	GLOBAL
	D-125	819S10	125	Ø125	1,6		
	D-150	819S11	150	Ø150	2,2		

On special request of Customer, it is possible to adapt a set of nozzles for double exhaust pipe assembly.


Suction stands for exhaust extractors

	Type	Part no.	Connection diameter [mm]	Inlet dimension [mm]	Weight [kg]	Remarks
	S-100-2	818S13	100	Ø230	14	Mobile nozzle on a stand with wheels, of aluminium.
	S-125-2	818S14	125	Ø230	15	
	S-152	818S04	150	260x205	17	Nozzle on a stand, of steel.

Nozzle Euro 5/6

	Type	Part no.	Connection diameter [mm]	Inlet dimension [mm]	Weight [kg]	Remarks
	Euro 5/6	819S35	150	400x250	13	Adjustable mobile nozzle on a stand with wheels, adapted for capturing the exhaust fume of exhaust pipes located underneath the vehicle.

Quick-connector

	Type	Part no.	Connection diameter [mm]	Weight [kg]	Remarks
	SZS-125/100	830S03	125/100	0,6	Quick-connector reduces the nozzle diameter and adapts it to another diameter of the hose.
	SZS-150/125	830S02	150/125	0,8	
	SZS-150/100	830S04	150/100	0,75	