










NOZZLES COOPERATING WITH EXHAUST EXTRACTORS



Below are listed all sorts of nozzles for exhaust extractors.

For selection take into account the diameter, material and accessories.


Sort of the nozzle	Type	Part No.	Connection diameter [mm]	Inlet dimension [mm]	Weight [kg]	Remarks	Cooperating devices
	SZGO-125	819S28	125	Ø150	2,5	rubber circular nozzle with lever pliers, for manual release	ALAN-N, OBS/P, OBP/P-AL, OBP/P, GLOBAL
	SZGO-150	819S29	150	Ø170	3,2		
	SZGP-100	819S18	100	180x100	2,1	rubber oval nozzle with lever pliers, for manual release	ALAN-N, OBS/P, OBP/P-AL, OBP/P, GLOBAL
	SZGP-125	819S19	125	180x100	3,2		
	SZGO-125/S	819S75	125	Ø150	2,5	rubber circular nozzle with lever pliers and steel cable, for automatic release	OBP/P
	SZGO-150/S	819S76	150	Ø170	3,2		
	SZGP-100/S	819S77	100	180x100	2,1	rubber oval nozzle with lever pliers and steel cable, for automatic release	OBP/P
	SZGP-125/S	819S78	125	180	3,2		
	SZGO-125/B	819S70	125	Ø150	2,5	rubber circular nozzle with lever pliers and Bowden cable, for automatic release	OBP/P-AL, OBP/P
	SZGO-150/B	819S71	150	Ø170	3,2		
	SZGP-100/B	819S72	100	180x100	2,1	rubber oval nozzle with lever pliers and Bowden cable, for automatic release	OBP/P-AL, OBP/P
	SZGP-125/B	819S73	125	180x100	3,2		
	SRGP-150-N	819S37	150	Ø175	2,9	rubber oval nozzle, for built-in and shielded exhaust pipes, for manual release (the pliers are inside the exhaust pipe)	ALAN-N, OBS/P, OBP/P-AL, OBP/P, GLOBAL
	AN-100	819S06	100	Ø125	1	metallic nozzle, clamped with a knob, for manual release	ALAN-N, OBS/P, GLOBAL
	AN-125	819S07	125	Ø125	1,2		
	AN-150	819S08	150	Ø150	1,45		
	AN-200	819S00	200	Ø200	2		
	D-150	819S11	150	Ø150	2,2	metallic nozzle, shut-off lid closed by a spring with, for manual release Ø100 and Ø125 mm	GLOBAL

On demand of Customer our nozzles can be adapted for double exhaust pipes.


SUCTION STANDS COOPERATING WITH EXHAUST EXTRACTORS

	Type	Part No.	Connection diameter [mm]	Inlet dimension [mm]	Weight [kg]	Remarks
	S-100-2	818S13	100	Ø230	14	a mobile nozzle on a stand displacing on wheels, execution of aluminium
	S-125-2	818S14	125	Ø230	15	
	S-152	818S04	150	260x205	17	a steel nozzle on a stand

NOZZLE EURO 5/6

	Type	Part No.	Connection diameter [mm]	Inlet dimension [mm]	Weight [kg]	Remarks
	Euro 5/6	819S35	150	400x250	13	An adjustable mobile nozzle on a stand displacing on wheels, adapted for extraction from exhaust pipes located under the vehicle. It is recommended to apply a hose of thermal resistance 300°C.

NOZZLE QUICK-CONNECTORS

	Type	Part No.	Connection diameter [mm]	Weight [kg]	Remarks
	SZS-125/100	830S03	125/100	0,6	Reduces the diameter of the nozzle to adapt it to another hose diameter.
	SZS-150/125	830S02	150/125	0,8	
	SZS-150/100	830S04	150/100	0,75	